

# SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)



## SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product name : E11 MATTE SURFACE CLEAN  
Product code : 41910

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Motorcycle cleaner

### 1.3. Details of the supplier of the safety data sheet

Registered company name : MOTUL  
Address : 119, Boulevard Felix Faure. 93300 AUBERVILLIERS CEDEX FRANCE  
Telephone : 33.1.48.11.70.00. Fax: 33.1.48.33.28.79. Telex: .  
Email : motul\_hse@motul.fr

### 1.4. Emergency telephone number : +44 (0) 1235 239 670.

Association/Organisation : CARECHEM 24/7 NCEC..

### Other emergency numbers

BRAZIL : +55 11 3197 5891 / COLOMBIA : +57 1 508 7337 / ARGENTINA : +54 11 5984 3690 / CHILE : +562 2582 9336  
Ireland : +353 1 8092566  
UNITED STATES: 001 866 928 0789 / CANADA: 001 800 579 7421 / MEXICO : +52 55 5004 8763 / MIDDLE EAST - AFRICA : +44 1235 239671  
24 hours a day, 7 days a week

## SECTION 2 : HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

#### In compliance with EC regulation No. 1272/2008 and its amendments.

Aerosol, Category 1 (Aerosol 1, H222 - H229).  
May produce an allergic reaction (EUH208).  
Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

### 2.2. Label elements

Detergent mixture (see section 15).  
Mixture for aerosol application.

#### In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS02

Signal Word :

DANGER

Additional labeling :

EUH208

Contains METHYLCHLOROISOTHIAZOLINONE, METHYLISOTHIAZOLINONE. May produce an allergic reaction.

Hazard statements :

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements - General :

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.

Precautionary statements - Prevention :

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.  
 P273 Avoid release to the environment.  
 Precautionary statements - Storage :  
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
 Precautionary statements - Disposal :  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**2.3. Other hazards**

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq 0.1\%$  published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>  
 The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

**SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS****3.2. Mixtures****Composition :**

Identification	(EC) 1272/2008	Note	%
CAS: 106-97-8 EC: 203-448-7 REACH: 01-2119474691-32  BUTANE	GHS02 Dgr Flam. Gas 1, H220 Press. Gas, H280	[1] [7]	2.5 $\leq$ x % < 10
CAS: 74-98-6 EC: 200-827-9  PROPANE	GHS02 Dgr Flam. Gas 1, H220 Press. Gas, H280	[1] [7]	1 $\leq$ x % < 2.5
CAS: 7632-00-0 EC: 231-555-9 REACH: 01-2119471836-27  SODIUM NITRITE	GHS06, GHS09, GHS03 Dgr Ox. Liq. 3, H272 Acute Tox. 3, H301 Eye Irrit. 2, H319 Aquatic Acute 1, H400 M Acute = 1		0 $\leq$ x % < 1
EC: 939-607-9 REACH: 01-2119977130-42  QUATERNARY AMMONIUM COMPOUNDS, C12-14 (EVEN-NUMBERED)-ALKYLETHYLDIMET HYL, ETHYL SULPHATES	GHS06, GHS05, GHS09 Dgr Acute Tox. 4, H302 Acute Tox. 3, H311 Skin Corr. 1C, H314 Aquatic Acute 1, H400 M Acute = 10 Aquatic Chronic 1, H410 M Chronic = 10		0 $\leq$ x % < 1
CAS: 55965-84-9  METHYLCHLOROISOTHIAZOLINONE, METHYLISOTHIAZOLINONE	GHS06, GHS05, GHS09 Dgr Acute Tox. 3, H301 Acute Tox. 2, H310 Skin Corr. 1B, H314 Skin Sens. 1, H317 Acute Tox. 2, H330 STOT SE 3, H335 Aquatic Acute 1, H400 M Acute = 100 Aquatic Chronic 1, H410 M Chronic = 100 EUH:071		0 $\leq$ x % < 1

(Full text of H-phrases: see section 16)

**Information on ingredients :**

[7] Propellant gas  
 [1] Substance for which maximum workplace exposure limits are available.

## SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

### 4.1. Description of first aid measures



#### In the event of exposure by inhalation :

In the event of an allergic reaction, seek medical attention.

Apply resuscitation techniques. Prolonged clinical monitoring may be necessary.



#### In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.



#### In the event of splashes or contact with skin :

In the event of an allergic reaction, seek medical attention.

Immediately remove all soiled clothing.

#### In the event of swallowing :

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

### 4.2. Most important symptoms and effects, both acute and delayed

No data available.

### 4.3. Indication of any immediate medical attention and special treatment needed

No data available.

## SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

### 5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

#### Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO<sub>2</sub>)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

#### Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet



### 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

### 5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

## SECTION 6 : ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

Spilled product may make surfaces slippery.

#### For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

#### For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).



### 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Use drums to dispose of collected waste in compliance with current regulations (see section 13).



### 6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

In case of accidental release neutralize with sand or inert material .....

### 6.4. Reference to other sections

No data available.

## SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.



### 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Remove contaminated clothing and protective equipment before entering eating areas.

Do not get in eyes, on skin, or on clothing.

Spray in short bursts, without prolonged spraying.

Follow standard health and safety rules on account of flammability.

#### Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.



#### Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not breathe in aerosols.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Ensure good ventilation at the workplace

Keep in original container. Do not pierce or burn, even after usage.

Storage and handling instructions applicable to pressurised gases.



#### Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

Never open the packages under pressure.

### 7.2. Conditions for safe storage, including any incompatibilities

No data available.

#### Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

#### Packaging

Always keep in packaging made of an identical material to the original.

### 7.3. Specific end use(s)

No data available.

**SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1. Control parameters****Occupational exposure limits :**

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8	1000 ppm				
74-98-6	1000 ppm				

- Germany - AGW (BAuA - TRGS 900, 08/08/2019) :

CAS	VME :	VME :	Excess	Notes
106-97-8		1000 ppm 2400 mg/m <sup>3</sup>		4(II)
74-98-6		1000 ppm 1800 mg/m <sup>3</sup>		4(II)

- France (INRS - ED984 / 2019-1487) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
106-97-8	800	1900	-	-	-	-

- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8	600 ppm 1450 mg/m <sup>3</sup>	750 ppm 1810 mg/m <sup>3</sup>		Carc	

**8.2. Exposure controls****Appropriate engineering controls**

Ensure adequate ventilation, if possible with extractor fans at work posts and appropriate general extraction.  
Personnel shall wear regularly laundered overalls.

**Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

**- Eye / face protection**

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

**- Hand protection**

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- PVA (Polyvinyl alcohol)

Recommended properties :

- Impervious gloves in accordance with standard EN ISO 374-2

**- Body protection**

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

**SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES****9.1. Information on basic physical and chemical properties****General information :**

Physical state :	Fluid liquid.
	Spray.

 **Important health, safety and environmental information**

pH :	Not stated.
	Slightly basic.
Boiling point/boiling range :	100 °C.
Vapour pressure (50°C) :	Below 110 kPa (1.10 bar).
Density :	= 1
Water solubility :	Soluble.
Melting point/melting range :	Not specified.
Self-ignition temperature :	400 °C.
Chemical combustion heat :	Not specified.
Inflammation time :	Not specified.
Deflagration density :	Not specified.
Inflammation distance :	Not specified.
Flame height :	Not specified.
Flame duration :	Not specified.

**9.2. Other information**

No data available.

**SECTION 10 : STABILITY AND REACTIVITY****10.1. Reactivity**

No data available.

**10.2. Chemical stability**

This mixture is stable under the recommended handling and storage conditions in section 7.

**10.3. Possibility of hazardous reactions**

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

 **10.4. Conditions to avoid**

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.


Avoid :

- heating
- heat
- frost
- accumulation of electrostatic charges.
- flames and hot surfaces

**10.5. Incompatible materials**

Keep away from :

- strong acids
- strong oxidising agents

 **10.6. Hazardous decomposition products**

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

**SECTION 11 : TOXICOLOGICAL INFORMATION** **11.1. Information on toxicological effects**

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Splashes in the eyes may cause irritation and reversible damage

**11.1.1. Substances** **Acute toxicity :**

METHYLCHLOROISOTHIAZOLINONE, METHYLISOTHIAZOLINONE (CAS: 55965-84-9)

Inhalation route (Dusts/mist) :	LC50 = 0.33 mg/l
	Species : Rat
	Duration of exposure : 4 h

SODIUM NITRITE (CAS: 7632-00-0)

Oral route : LD50 = 180 mg/kg  
Species : Rat**Serious damage to eyes/eye irritation :**

SODIUM NITRITE (CAS: 7632-00-0)

Causes serious eye irritation.

Corneal haze : 1 <= Average score < 2 and effects totally reversible within 21 days of observation  
Species : Rabbit  
OCDE Ligne directrice 405 (Effet irritant/corrosif aigu sur les yeux)**11.1.2. Mixture****Respiratory or skin sensitisation :**

Contains at least one sensitising substance. May cause an allergic reaction.

 **SECTION 12 : ECOLOGICAL INFORMATION**

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

**12.1. Toxicity****12.1.1. Substances**

METHYLCHLOROISOTHIAZOLINONE, METHYLISOTHIAZOLINONE (CAS: 55965-84-9)

Fish toxicity : 0.001 < LC50 <= 0.01 mg/l  
Factor M = 100  
Duration of exposure : 96 h0,00001 < NOEC <= 0,0001 mg/l  
Factor M = 100

QUATERNARY AMMONIUM COMPOUNDS, C12-14 (EVEN-NUMBERED)-ALKYLETHYLDIMETHYL, ETHYL SULPHATES

Fish toxicity : LC50 = 13.8 mg/l  
Species : Danio rerio  
Duration of exposure : 96 h  
OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë)  
  
NOEC = 0.032 mg/l  
OCDE Ligne directrice 210 (Poisson, essai de toxicité aux premiers stades de la vie)Crustacean toxicity : EC50 = 0.036 mg/l  
Factor M = 10  
Species : Daphnia magna  
Duration of exposure : 48 h  
OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate)NOEC = 0.0007 mg/l  
Factor M = 10  
Species : Daphnia magna  
OCDE Ligne directrice 211 (Daphnia magna, essai de reproduction)

SODIUM NITRITE (CAS: 7632-00-0)

Fish toxicity : LC50 >= 0.54 mg/l  
Factor M = 1  
Species : Oncorhynchus mykiss  
Duration of exposure : 96 h**12.1.2. Mixtures**

No aquatic toxicity data available for the mixture.

**12.2. Persistence and degradability****12.2.1. Substances**

METHYLCHLOROISOTHIAZOLINONE, METHYLISOTHIAZOLINONE (CAS: 55965-84-9)

Biodegradability : Rapidly degradable.

QUATERNARY AMMONIUM COMPOUNDS, C12-14 (EVEN-NUMBERED)-ALKYLETHYLDIMETHYL, ETHYL SULPHATES  
Biodegradability : Rapidly degradable.SODIUM NITRITE (CAS: 7632-00-0)  
Biodegradability : Rapidly degradable.**12.3. Bioaccumulative potential**

No data available.

**12.4. Mobility in soil**

Water soluble

**12.5. Results of PBT and vPvB assessment**

No data available.

**12.6. Other adverse effects**

Do not dispose of the product in the natural environment, effluents or surface waters.

**German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :**

WGK 2 : Hazardous for water.

**SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

**13.1. Waste treatment methods**

Do not pour into drains or waterways.

**Waste :**

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

**SECTION 14 : TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2019 - IMDG 2018 - ICAO/IATA 2019).

**14.1. UN number**

1950

**14.2. UN proper shipping name**

UN1950=AEROSOLS, flammable

**14.3. Transport hazard class(es)**

- Classification :



2.1

**14.4. Packing group**

-

**14.5. Environmental hazards**

-

**14.6. Special precautions for user**

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	2	5F	-	2.1	-	1 L	190 327 344 625	E0	2	D
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregati on	

	2	See SP63	-	See SP277	F-D, S-U	63 190 277 327 344 381 959	E0	- SW1 SW22	SG69
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	2.1	2.1	-	203	75 kg	203	150 kg	A145 A167 A802	E0
	2.1	2.1	-	Y203	30 kg G	-	-	A145 A167 A802	E0

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

## SECTION 15 : REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### - Classification and labelling information included in section 2:

The following regulations have been used:

- Directive 75/324/CEE modified by directive 2013/10/UE
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2018/1480 (ATP 13)

#### - Container information:

No data available.

#### - Particular provisions :

Total net weight of the aerosol (active product + gas) : 371 g

#### - Labelling for detergents (EC Regulation No. 648/2004,907/2006) :


- 5 % or over but less than 15 % : aliphatic hydrocarbons
- perfumes
- preservation agents
- methylchloroisothiazolinone, methylisothiazolinone
- allergenic fragrances :
- alpha-hexyl cinnamic aldehyde

#### - German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :

WGK 2 : Hazardous for water.

#### - Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704) :

NFPA 704, Labelling: Health=0 Inflammability=1 Instability/Reactivity=1 Specific Risk=none



### 15.2. Chemical safety assessment

No data available.

## SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

#### Wording of the phrases mentioned in section 3 :

H220	Extremely flammable gas.
------	--------------------------

H272	May intensify fire; oxidiser.
H280	Contains gas under pressure; may explode if heated.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

**Abbreviations :**

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

GHS02 : Flame

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.